



Technical specifications

Electrical - control unit

Mains Electrical Supply	- Single Phase 3 Wire (Live-Neutral-Earth)
Supply Voltage	- 90—264V a.c.
Supply Frequency	- 47—64 Hz
Connected Load	- 40 VA
Circuit Protection	- 0.6 A Miniature Circuit Breakers—Live & Neutral
No. of Outputs to Applicators	- 1 or 2 Applicators
Output Voltage to Applicators	- 3.5—13V d.c.
Output Current to Applicators	- 400mA Max
Protection Category	- IP54 (IP65 when fitted into an SAS designed cabinet)
Operating Temperature	- 10°C/+60°C

Pneumatic - control unit

Compressed Air Supply	- 8 Bar (114psi) Max / 5 Bar (75psi) Min
Compressed Air Consumption	- 10m ³ /hr (6 c.f.m.) per Applicator
Max Water Vapour Content	- 1.3g/m ³
Max Oil Vapour Content	- 0.1 p.p.m.
Regulated Air Output	- 0-4 Bar

Electrostatic generating head

Supply Voltage	- 3.5—13V dc
Supply Current	- 400mA Max
Output Voltage	- 20-85kV
Output Current	- 50uA Max
Protection Category	- 1P65
Operating Temperatures	- -10°C+60°C

Spice Application Systems is a world leader in the application of electrostatic technology

Spice Application Systems Ltd
 PO Box 1190, Oxford OX4 4GH,
 England, UK
 Tel: +44 1865 747634
 Fax: +44 8701 602755

Email: info@spiceapplications.com
 Web: www.spiceapplications.com
 Company Registration number:
 3780320 (England)
 VAT No. GB 718 1526 40

**Spice
 Application
 Systems Ltd**